

Fusion Pro® Single Component® Grout

1 Product Name

Fusion Pro® Single Component® Grout

2 Manufacturer

Custom Building Products
 Technical Services
 10400 Pioneer Boulevard, Unit 3
 Santa Fe Springs, CA 90670
 Customer Support: 800-272-8786
 Technical Services: 800-282-8786
 Fax: 800- 200-7765
 Email: contactus@cbpmail.net
custombuildingproducts.com

3 Product Description

Fusion Pro® - the original stain proof, color perfect grout.* This professional grade sanded grout features unsurpassed stain resistance with no sealing required. Its Single Component® formula is ready to use and easy to spread and clean. Fusion Pro can be installed in commercial and residential environments, interiors and exteriors, and on walls and floors and specifically shower floors. Its patented formulation can be applied on all tiles and has built-in Microban antimicrobial product protection. *See warranty for details.

Key Features

- Stain proof and color perfect
- Unsurpassed performance
- Never needs sealing
- Easy to spread and clean
- Ready-to-use

Uses

- Use to fill joint widths 1/16" to 1/2" (1.6-13 mm)
- May be used for both floor and wall installations
- Exterior and interior applications.
- Commercial and residential applications
- Countertops, tub surrounds, shower walls and floors and high traffic areas

Suitable Tile Types

- Vitreous, semi-vitreous or non-vitreous tile: ceramic, mosaic, quarry, cement body tile
- Impervious porcelain and glass tile
- Cement-based precast terrazzo
- Polished, natural stone
- Groutable luxury vinyl tile

Composition of Product

Advanced polymers with inorganic fillers and pigments.



Benefits of Product in the Installation

- Stain proof grout
- No sealing required
- Ready to use
- Hard, durable grout joints
- No efflorescence
- Crack resistant
- MicroBan® antimicrobial product protection

Limitations to the Product

- Should not be installed when ambient or surface temperature is lower than 50° F (10° C) or above 90° F (32° C).
- Some ceramic, glass, metal, marble or stone tiles can be scratched or damaged by the silica aggregate filler. Perform a test on a small area prior to use.
- Tile or stone with high absorption, surfaces that are porous or rough, textured surfaces and some types of porcelain tile generally require sealing prior to grouting to prevent possible staining.
- Do not use Fusion Pro with irregularly shaped or spaced tile or stone, such as pebble stones, where joint widths or depths exceed 1/2".
- Not for use in either industrial applications or in areas subjected to harsh or continuous chemicals, high heat or high-pressure cleaning. For heavy industrial tile installations, use [CEG-IG 100% Solids Epoxy Grout](#).
- Not for use over concrete slabs with high moisture emission rates.
- Not for use in steam rooms or submerged applications (swimming pools, spas, water features and fountains).
- Not for use in movement joints or changes of plane in the tile installation. In these areas use an appropriate caulk or sealant such as [Commercial 100% Silicone Caulk](#) or [Polyblend® Ceramic Tile Caulk](#).

Packaging

- All colors available in 1 gallon pails.
- Select colors available in 1 quart pails.
- Available in 40 standard colors.



Fusion Pro® Single Component® Grout

4 Technical Data

Approvals

Meets the performance characteristics of A118.7 and A118.3.

Technical Chart

Tests	Method	Results
Hardness at 28 days	ASTM D 2240 (Shore D)	76
Compressibility (psi grout joint)	CBP Method	3380
Shrinkage	CBP Method	0.013
Stain	CTIOA T-72- MODIFIED	0.5-1
Cleanability	as per 118.3	Pass
Chem Resistance	ASTM C267	Pass
Vertical Joint Sag	as per 118.3	Pass

Environmental Consideration

Custom® Building Products is committed to environmental responsibility in both products produced and in manufacturing practices. Use of this product can contribute towards LEED® v3 certification:

- Up to 2 points towards MR Credit 5, Regional Materials
- Up to 1 point towards IEQ Credit 4.1, Low-Emitting Materials – Adhesives & Sealants

5 Instructions

General Surface Prep

USE CHEMICAL-RESISTANT GLOVES, such as nitrile, when handling product.

Tiled surface and joints must be clean, and adhesives must be dry. When grouting both vertical and horizontal substrates together, protect horizontal substrate from excess wash water that may fall during the cleaning of grout on walls by covering the floor area prior to grout installation on the walls.

Mixing Procedures

Ready to use – no mixing required. Do not use power mixer - will cause weaker joints.

Application of Product

- Pre-seal natural stones and porous or rough textured tile with [Aqua Mix® Grout Release](#), [Aqua Mix® Sealer's Choice® Gold](#) or [TileLab® SurfaceGard®](#).
- Fusion Pro cures by evaporation. Ensure setting material has dried sufficiently, substrate does not have a high moisture emission rate and work area has adequate ventilation.
- Only spread for 1-2 minutes, typically 10 sq. ft. (0.9 m²) before cleaning grout off the tile surface. More can be spread in cool, damp conditions; less in hot, dry conditions.
- Do not allow Fusion Pro to dry or skin over prior to final cleaning. If grout dries on surface during installation, lightly moisten and wait 2-4 minutes, then gently clean tile surface using sponge or white nylon scrubber.

Download the Fusion Pro Installation Guide on our website for additional details.

Fusion Pro is a new technology grout with significant advantages over traditional grouts, requiring modified installation techniques to achieve best results. Do not apply or clean up this grout as typically done with cement or epoxy grout.

Lightly dampen tile surface before spreading. Do not allow any water to puddle on the surface of the tile or in the grout joints. Use a medium to hard grout float to spread grout. Spread grout and fill joints for 2 minutes, typically 10 sq. ft. (0.9 m²) increments. More grout can be spread in cool, damp conditions; less in hot, dry conditions. Drag the edge of the float diagonally across the tile to remove excess grout while leaving the joints full. Cleaning of grouted area should begin immediately, before grouting next section.

Use a lightly damp grout sponge held flat against the tile. Working the entire 10 sq. ft. area, use a circular motion and moderate pressure to loosen any grout that is still adhered to the tile surface. Limit the number of times you rinse out the sponge at this stage. The residue on the sponge will help break up and soften residue on the surface of the tile. Do not over scrub as it may pull grout out of the joints. Grout joints must remain full. In areas where the Fusion Pro is well-adhered, leaving a visible film that is not releasing from the surface of the tile, re-apply a small amount of Fusion Pro. Slurry the grout with the clean up sponge until clean (approximately 30 seconds). Wipe the area clean with a rinsed, lightly damp sponge, followed by a lightly damp microfiber towel.

Once grout on tiled surfaces has been loosened, thoroughly rinse and wring out the sponge. Wipe the sponge once across the grouted tile diagonally to clean the face of the tile and create smooth consistent grout joints. Flip the sponge over and continue cleaning the next area. Rinse, wring and repeat until you have dragged a clean sponge face across the entire 10 sq. ft. area of freshly grouted tile.

Lastly, drag a lightly damp microfiber towel across the surface for final clean up. Do not allow Fusion Pro to dry or skin over prior to final cleaning. If grout dries on the surface, lightly moisten and wait 2-4 minutes, then gently clean the tile surface using a sponge (or a white nylon scrubber) to remove residue. If streaks or residue remain after 2 hours, use diluted [Aqua Mix® Grout Haze Clean-Up](#), [Aqua Mix® Non-Cement Grout Haze Remover](#), [TileLab® Grout & Tile Cleaner](#) or [TileLab® Heavy Duty Stripper & Cleaner](#) and clean with a sponge or scrub pad. Additional instruction and videos available online.

Curing of Product

Allow 24 hrs until light traffic, and 7 days at 70° F (21° C) and 50% relative humidity before intermittent water exposure (such as a shower enclosure). Lower temperatures and higher humidity will slow the cure times. Covering Fusion Pro immediately after grouting will extend the cure time. Grout should be allowed to cure 24 hours before covering with a highly-porous protective material to ensure a timely cure to protect the surface from other trades traffic. Lower temperatures and higher humidity will slow cure times. Exterior applications must be protected from rain, snow and other wet conditions for at least 7 days with temperature above 50° F (10° C). If inclement weather is expected, protect the work area with tenting at least 1 foot (30 cm) above the finished surface to allow air flow. Enclose and protect exterior installations and maintain >50° F (10° C) temperatures for at least 72 hours for proper cure.

Sealing of Tile Assembly



Fusion Pro® Single Component® Grout

Fusion Pro grout is a stain resistant grout. Sealing is not necessary. If sealing of the tile is necessary, use a water based sealer like AquaMix Sealer's Choice Gold and wipe off excess on grout joints. Do not use solvent-based sealers or enhancers with Fusion Pro.

Cleaning of equipment

Clean tools and hands with water before material dries.

Health Precautions

Contains ethylene glycol, 2-butoxy ethanol and acrylic latex. Avoid contact with eyes and skin. Do not take internally. CAUTION: KEEP OUT OF REACH OF CHILDREN. Use in well-ventilated areas. Wear chemical resistant gloves and eye protection. FIRST AID: If eye or skin contact, flush thoroughly with water. In case of respiratory tract irritation, move person to fresh air. If irritation persists, seek medical attention. If ingested, do not induce vomiting. Seek medical attention. This product contains a chemical or chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

6 Availability & Cost

Item Code	Size	Grout Color	Package
FP091-2T	1 gal (3.78 L)	#9 Natural Gray	Pail
FP101-2T	1 gal (3.78 L)	#10 Antique White	Pail
FP111-2T	1 gal (3.78 L)	#11 Snow White	Pail
FP191-2T	1 gal (3.78 L)	#19 Pewter	Pail
FP221-2T	1 gal (3.78 L)	#22 Sahara Tan	Pail
FP451-2T	1 gal (3.78 L)	#45 Summer Wheat	Pail
FP501-2T	1 gal (3.78 L)	#50 Nutmeg	Pail
FP521-2T	1 gal (3.78 L)	#52 Tobacco Brown	Pail
FP591-2T	1 gal (3.78 L)	#59 Saddle Brown	Pail
FP601-2T	1 gal (3.78 L)	#60 Charcoal	Pail
FP951-2T	1 gal (3.78 L)	#95 Sable Brown	Pail
FP1011-2T	1 gal (3.78 L)	#101 Quartz	Pail
FP1051-2T	1 gal (3.78 L)	#105 Earth	Pail
FP1151-2T	1 gal (3.78 L)	#115 Platinum	Pail
FP1221-2T	1 gal (3.78 L)	#122 Linen	Pail
FP1351-2T	1 gal (3.78 L)	#135 Mushroom	Pail
FP1451-2T	1 gal (3.78 L)	#145 Light Smoke	Pail
FP1561-2T	1 gal (3.78 L)	#156 Fawn	Pail
FP1651-2T	1 gal (3.78 L)	#165 Delorean Gray	Pail
FP1721-2T	1 gal (3.78 L)	#172 Urban Putty	Pail
FP1801-2T	1 gal (3.78 L)	#180 Sandstone	Pail
FP1831-2T	1 gal (3.78 L)	#183 Chateau	Pail
FP1851-2T	1 gal (3.78 L)	#185 New Taupe	Pail
FP1861-2T	1 gal (3.78 L)	#186 Khaki	Pail
FP3331-2T	1 gal (3.78 L)	#333 Alabaster	Pail
FP3351-2T	1 gal (3.78 L)	#335 Winter Gray	Pail
FP3701-2T	1 gal (3.78 L)	#370 Dove Gray	Pail
FP3801-2T	1 gal (3.78 L)	#380 Haystack	Pail
FP3811-2T	1 gal (3.78 L)	#381 Bright White	Pail
FP3821-2T	1 gal (3.78 L)	#382 Bone	Pail
FP3861-2T	1 gal (3.78 L)	#386 Oyster Gray	Pail
FP4011-2T	1 gal (3.78 L)	#540 Truffle	Pail
FP5411-2T	1 gal (3.78 L)	#541 Walnut	Pail
FP5421-2T	1 gal (3.78 L)	#542 Graystone	Pail
FP5431-2T	1 gal (3.78 L)	#543 Driftwood	Pail
FP5441-2T	1 gal (3.78 L)	#544 Rolling Fog	Pail
FP5451-2T	1 gal (3.78 L)	#545 Bleached Wood	Pail
FP5461-2T	1 gal (3.78 L)	#546 Cape Gray	Pail
FP5471-2T	1 gal (3.78 L)	#547 Ice Blue	Pail
FP5481-2T	1 gal (3.78 L)	#548 Surf Green	Pail

Select colors are also available in a quart size container.



CUSTOM®

Fusion Pro® Single Component® Grout

The following colors are discontinued as of March 2015: #92 Admiral Blue, #96 Quarry Red Clay, #99 Burnt Clay, #127 Antique Linen, #168 Slate Gray, #190 Bay Leaf, #301 Arctic Ice, #305 Onyx Green, #311 Moss, #312 Bonsai, #365 Canvas, #384 Camel, #390 Rose Beige

See our color card for truest color representation when selecting or specifying a grout color. Final installed shade may vary with the tile type, color and porosity as well as jobsite conditions and finishing techniques. For best results, perform a test on a small, inconspicuous area or create a sample board prior to installation.

Commercial 100% Silicone Sealant

Aqua Mix® Grout Haze Clean-Up

Aqua Mix® Grout Release

Fusion Pro® Single Component® Grout Designer Series

TileLab® Grout & Tile Cleaner

7 Product Warranty

Custom® Building Products warrants to the original consumer/purchaser that Fusion Pro® Single Component® Grout shall be free from color fading; staining; shrinkage cracking; mold growth within the product; and break down in wet environments due to defects in material and workmanship under normal and proper usage for a period of five (5) years following the date of original purchase. Custom's® sole liability under this warranty shall be limited to the replacement of the product. Some states, countries or territories do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with Custom's® printed instructions. Custom® makes no other warranties either expressed or implied. This warranty gives you specific legal rights, and you may have other rights that vary from state to state or from one country/territory to another. This warranty is not transferrable.

Also see our [Fusion Pro Stain Proof, Color Perfect warranty here](#).

When Fusion Pro® Single Component® Grout is used as a part of a qualifying full installation system of CUSTOM products, the installation can qualify for up to a lifetime system warranty. CUSTOM will repair and/or replace, at its discretion, the affected area of the system. For more information, find details and limitations to this warranty at custombuildingproducts.com.

8 Product Maintenance

Clean with a neutral cleaner such as [Aqua Mix AquaKleen](#), [Aqua Mix Concentrated Stone & Tile Cleaner](#) or [Tilelab Grout & Tile Cleaner](#).

9 Technical Services Information

For technical assistance, contact Custom technical services at 800-282-8786 or visit custombuildingproducts.com.

10 Filing System

Additional product information is available from the manufacturer upon request.

Also refer to CUSTOM Technical Bulletins:

- TB57: Grout Maintenance
- TB77: Installing Fusion Pro
- TB85: Grout Joint Width Considerations
- TB86: Grout Joints Less than 1/8"

Handling & Storage

Protect grout from freezing. If product freezes, return to room temperature and use as directed. Do not stir if partially frozen.

Related Products

Polyblend® Ceramic Tile Caulk

Published Date: 8/3/2017



CUSTOM®

Fusion Pro® Single Component® Grout

Coverage

1 gallon pail of Fusion Pro Grout in ft² (m²) per gallon

Tile Size Width x Length x Thickness	Joint Width					
	1/16" (1.6 mm)	1/8" (3 mm)	3/16" (4.8 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4" (2.5 x 2.5 x .64 cm)	55 ft ² (5.1 m ²)	31 ft ² (2.9 m ²)	23 ft ² (2.1 m ²)	19 ft ² (1.8 m ²)	15 ft ² (1.4 m ²)	14 ft ² (1.3 m ²)
2" x 2" x 1/4" (5 x 5 x .64 cm)	103 ft ² (9.6 m ²)	55 ft ² (5.1 m ²)	39 ft ² (3.6 m ²)	31 ft ² (2.9 m ²)	23 ft ² (2.1 m ²)	19 ft ² (1.8 m ²)
3" x 3" x 1/4" (7.6 x 7.6 x .64 cm)	152 ft ² (14.1 m ²)	79 ft ² (7.3 m ²)	55 ft ² (5.1 m ²)	43 ft ² (4 m ²)	31 ft ² (2.9 m ²)	25 ft ² (2.3 m ²)
4.25" x 4.25" x 1/4" (10.8 x 10.8 x .64 cm)	213 ft ² (19.8 m ²)	110 ft ² (10.2 m ²)	75 ft ² (7.0 m ²)	58 ft ² (5.4 m ²)	41 ft ² (3.8 m ²)	32 ft ² (3.0 m ²)
6" x 6" x 1/4" (15.2 x 15.2 x .64 cm)	298 ft ² (27.7 m ²)	152 ft ² (14.1 m ²)	103 ft ² (9.6 m ²)	79 ft ² (7.4 m ²)	55 ft ² (5.1 m ²)	43 ft ² (4.0 m ²)
8" x 8" x 3/8" (20.3 x 20.3 x 1 cm)	263 ft ² (24.4 m ²)	134 ft ² (12.4 m ²)	91 ft ² (8.5 m ²)	69 ft ² (6.4 m ²)	47 ft ² (4.4 m ²)	37 ft ² (3.4 m ²)
12" x 12" x 3/8" (30.5 x 30.5 x 1 cm)	393 ft ² (36.5 m ²)	199 ft ² (18.5 m ²)	134 ft ² (12.4 m ²)	101 ft ² (9.4 m ²)	69 ft ² (6.4 m ²)	53 ft ² (4.9 m ²)
16" x 16" x 3/8" (40.6 x 40.6 x 1 cm)	523 ft ² (48.6 m ²)	263 ft ² (24.4 m ²)	177 ft ² (16.4 m ²)	134 ft ² (12.4 m ²)	91 ft ² (8.5 m ²)	69 ft ² (6.4 m ²)
18" x 18" x 3/8" (45.7 x 45.7 x 1 cm)	588 ft ² (54.6 m ²)	296 ft ² (27.5 m ²)	199 ft ² (18.5 m ²)	150 ft ² (13.9 m ²)	101 ft ² (9.4 m ²)	77 ft ² (7.2 m ²)
20" x 20" x 3/8" (50.8 x 50.8 x 1 cm)	653 ft ² (60.7 m ²)	328 ft ² (30.5 m ²)	220 ft ² (20.4 m ²)	166 ft ² (15.4 m ²)	112 ft ² (10.4 m ²)	85 ft ² (7.9 m ²)
24" x 24" x 3/8" (61 x 61 x 1 cm)	782 ft ² (72.6 m ²)	393 ft ² (36.5 m ²)	263 ft ² (24.4 m ²)	199 ft ² (18.5 m ²)	134 ft ² (12.4 m ²)	101 ft ² (9.4 m ²)
6" x 24" x 3/8" (15.2 x 61 x 1 cm)	315 ft ² (29.3 m ²)	160 ft ² (14.8 m ²)	108 ft ² (10 m ²)	82 ft ² (7.6 m ²)	56 ft ² (5.2 m ²)	43 ft ² (4.0 m ²)
12" x 24" x 3/8" (30.5 x 61 x 1 cm)	523 ft ² (48.6 m ²)	263 ft ² (24.5 m ²)	177 ft ² (16.4 m ²)	134 ft ² (12.4 m ²)	91 ft ² (8.4 m ²)	69 ft ² (6.4 m ²)
6" x 36" x 3/8" (15.2 x 91.4 x 1 cm)	338 ft ² (31.4 m ²)	171 ft ² (15.9 m ²)	115 ft ² (10.7 m ²)	87 ft ² (8.1 m ²)	60 ft ² (5.6 m ²)	46 ft ² (4.3 m ²)
9 x 36" x 3/8" (22.9 x 91.4 x 1 cm)	471 ft ² (43.8 m ²)	238 ft ² (22.1 m ²)	160 ft ² (14.9 m ²)	121 ft ² (11.2 m ²)	82 ft ² (7.6 m ²)	62 ft ² (5.8 m ²)
12" x 48" x 3/8" (30.5 x 122 x 1 cm)	627 ft ² (58.2 m ²)	315 ft ² (29.3 m ²)	212 ft ² (19.7 m ²)	160 ft ² (14.9 m ²)	108 ft ² (10 m ²)	82 ft ² (7.6 m ²)

1 quart pail of Fusion Pro Grout in ft² (m²) per quart



CUSTOM®

Fusion Pro® Single Component® Grout

Tile Size Width x Length x Thickness	Joint Width					
	1/16" (1.6 mm)	1/8" (3 mm)	3/16" (4.8 mm)	1/4" (6.3 mm)	3/8" (9.5 mm)	1/2" (13 mm)
1" x 1" x 1/4" (2.5 x 2.5 x .64 cm)	14 ft ² (1.3 m ²)	8 ft ² (0.7 m ²)	6 ft ² (0.5 m ²)	5 ft ² (0.4 m ²)	4 ft ² (0.4 m ²)	3 ft ² (0.3 m ²)
2" x 2" x 1/4" (5 x 5 x .64 cm)	26 ft ² (2.4 m ²)	14 ft ² (1.3 m ²)	10 ft ² (0.9 m ²)	8 ft ² (0.7 m ²)	6 ft ² (0.5 m ²)	5 ft ² (0.4 m ²)
3" x 3" x 1/4" (7.6 x 7.6 x .64 cm)	38 ft ² (3.5 m ²)	20 ft ² (1.8 m ²)	13.8 ft ² (1.3 m ²)	10.8 ft ² (1 m ²)	7.8 ft ² (0.7 m ²)	6.3 ft ² (0.6 m ²)
4.25" x 4.25" x 1/4" (10.8 x 10.8 x .64 cm)	53 ft ² (4.9 m ²)	28 ft ² (2.5 m ²)	19 ft ² (1.7 m ²)	14 ft ² (1.3 m ²)	10 ft ² (0.9 m ²)	8 ft ² (0.7 m ²)
6" x 6" x 1/4" (15.2 x 15.2 x .64 cm)	74 ft ² (6.9 m ²)	38 ft ² (3.5 m ²)	26 ft ² (2.4 m ²)	20 ft ² (1.8 m ²)	14 ft ² (1.3 m ²)	11 ft ² (1 m ²)
8" x 8" x 3/8" (20.3 x 20.3 x 1 cm)	66 ft ² (6.1 m ²)	34 ft ² (3.1 m ²)	23 ft ² (2.1 m ²)	17 ft ² (1.6 m ²)	12 ft ² (1.1 m ²)	9 ft ² (0.9 m ²)
12" x 12" x 3/8" (30.5 x 30.5 x 1 cm)	98 ft ² (9.1 m ²)	50 ft ² (4.6 m ²)	34 ft ² (3.1 m ²)	25 ft ² (2.4 m ²)	17 ft ² (1.6 m ²)	13 ft ² (1.2 m ²)
16" x 16" x 3/8" (40.6 x 40.6 x 1 cm)	131 ft ² (12.1 m ²)	66 ft ² (6.1 m ²)	44 ft ² (4.1 m ²)	33 ft ² (3.1 m ²)	23 ft ² (8.5 m ²)	17 ft ² (1.6 m ²)
18" x 18" x 3/8" (45.7 x 45.7 x 1 cm)	147 ft ² (13.7 m ²)	74 ft ² (6.9 m ²)	50 ft ² (4.6 m ²)	38 ft ² (3.5 m ²)	25 ft ² (2.4 m ²)	19 ft ² (1.8 m ²)
20" x 20" x 3/8" (50.8 x 50.8 x 1 cm)	163 ft ² (15 m ²)	82 ft ² (7.6 m ²)	55 ft ² (5.1 m ²)	42 ft ² (3.9 m ²)	28 ft ² (2.6 m ²)	21 ft ² (2 m ²)
24" x 24" x 3/8" (61 x 61 x 1 cm)	196 ft ² (18 m ²)	98 ft ² (9.1 m ²)	66 ft ² (6.1 m ²)	50 ft ² (4.6 m ²)	34 ft ² (3.1 m ²)	25 ft ² (2.3 m ²)
6" x 24" x 3/8" (15.2 x 61 x 1 cm)	79 ft ² (7.3 m ²)	40 ft ² (3.7 m ²)	27 ft ² (2.5 m ²)	20 ft ² (1.9 m ²)	14 ft ² (1.3 m ²)	11 ft ² (1 m ²)
12" x 24" x 3/8" (30.5 x 61 x 1 cm)	131 ft ² (12.1 m ²)	66 ft ² (6.1 m ²)	44 ft ² (4.1 m ²)	33 ft ² (3.1 m ²)	23 ft ² (2.1 m ²)	17 ft ² (1.6 m ²)
6" x 36" x 3/8" (15.2 x 91.4 x 1 cm)	85 ft ² (7.9 m ²)	43 ft ² (4 m ²)	29 ft ² (2.7 m ²)	22 ft ² (2 m ²)	15 ft ² (1.4 m ²)	11.5 ft ² (1.1 m ²)
9 x 36" x 3/8" (22.9 x 91.4 x 1 cm)	118 ft ² (10.9 m ²)	60 ft ² (5.5 m ²)	40 ft ² (3.7 m ²)	30 ft ² (2.8 m ²)	21 ft ² (1.9 m ²)	15.5 ft ² (1.4 m ²)
12" x 48" x 3/8" (30.5 x 122 x 1 cm)	157 ft ² (14.6 m ²)	79 ft ² (7.3 m ²)	53 ft ² (4.9 m ²)	40 ft ² (3.7 m ²)	27 ft ² (2.5 m ²)	20.5 ft ² (1.9 m ²)

Chart for estimating purposes. Coverage may vary based on installation practices and jobsite conditions. For more tile and joint sizes, use the [Material Calculator](#) at CustomBuildingProducts.com or contact CUSTOM Technical Services at [800-282-8786](tel:800-282-8786).



CUSTOM®