


WATERPROOFING & TILING WALLS AND FLOORS IN WET AREAS

No: D-1004

Revision: 2

Issued: Jul 10, 2026



1 Bondbreaker

WP MS-PU
Polyurethane
Sealant



2 Bandage (optional)

WP Bandage

FLEXI Bandage



3 Waterproofing

WP-1 PINK
Class III SBR
Waterproofing
Membrane



4 Screed

SCR-100
Engineered Screed



5 Tile Adhesive

ADH-33
ADH-44
ADH-55
ADH-66



6 Grout

Spectrum Futura
Lightweight
Coloured Grout



7 Silicone

Spectrum Futura S-25
Sanitary Grade
Acetoxy Silicone



8 Tile Levelling

EZE-Clip
Tile Laying
System



This document provides general recommendations only and is designed to be used in combination with relevant Product Data Sheets, standards and industry practices. As each project differs in requirements and site conditions, specific recommendations may vary from the information provided here. For recommendations related to a specific project, please, contact ACT Australia Pty Ltd.



WATERPROOFING & TILING WALLS AND FLOORS IN WET AREAS

No: D-1004
Revision: 2
Issued: Jul 10, 2026

INFORMATION

SCOPE

This specification outlines general guides for the materials selection, preparation, application, and installation for the tiling systems within internal and external covered wet areas (e.g. bathrooms, laundries, balconies).

STANDARDS & CODES

All work shall comply with the latest editions of the following standards and documents:

- AS 3740 – Waterproofing of domestic wet areas
- AS 3958.1 – Ceramic tiles – Guide to the installation of ceramic tiles
- AS 4858 – Wet area membranes
- National Construction Code (NCC)
- Building Code of Australia (BCA)
- Any other relevant building codes
- Relevant Product Data Sheets and installation guides

INSTALLATION GUIDE

1 SUBSTRATE PREPARATION

Ensure substrate is clean, dry, and free from dust, oil, and contaminants. Surface must be structurally sound.

Optional:

PR-2 - if substrate is highly porous or remains dusty.
Follow application instructions on packaging and PDS.

PR-2 Green
Multipurpose
Acrylic Primer



2 WATERPROOFING - Under Screed

Use **WP MS-PU Polyurethane Sealant** as a bond breaker in the corners, FC Sheet joints, structural joints etc.

Optional:

Apply **WP Bandage** or **FLEXI Bandage** as reinforcement to the bond breaker.

WP MS-PU
Polyurethane
Sealant



WP Bandage
FLEXI Bandage



Apply minimum 2 coats of **WP-1 PINK** waterproofing membrane.

Follow application instructions on packaging and PDS.

WP-1 PINK
Class III SBR
Waterproofing
Membrane



3 SCREED

Use **SCR-100 Engineered Screed** to create required falls to the drains.

Ensure that the screed mixture is applied to wet slurry coat as per installation instructions. For slurry coat, mix ADH-55 high polymer tile adhesive to slurry consistency.

Follow application instructions on packaging and PDS.

SCR-100
Engineered Screed



WATERPROOFING & TILING WALLS AND FLOORS IN WET AREAS

No: D-1004

Revision: 2

Issued: Jul 10, 2026

INSTALLATION GUIDE

4 WATERPROOFING - Over Screed (optional)

If waterproofing over screed is required by the relevant standards, guidelines or project specifications, repeat step 2 over screed.

If faster drying time is required, use **EP-2 Epoxy Membrane** instead of **WP-1 PINK**.

Follow application instructions on packaging and PDS.

5 TILE INSTALLATION

Use appropriate size notched trowel based on the size of the tiles. Follow mixing, application and drying instructions on packaging and PDS.

ADH-33 - rubber modified tile adhesive with high coverage. Ideal for large floor areas.

ADH-44 - versatile powder mastic for walls and floors with great workability and non-slump properties. Suitable for most internal and external applications.

ADH-55 - high polymer content tile adhesive with increased coverage, higher bond strength and flexibility. Best for large format floor tiles.

ADH-66 - lightweight tile adhesive with highest adhesion strength and improved non-slump properties. Best for large format tiles on walls and floors.

For a perfect tiled surface finish, use ACT's patented **EZE-Clip** Tile Laying System.

6 GROUT & SILICONE

Choose from a wide range of colours of **Spectrum Futura** Lightweight Coloured Grout suitable for joints from 1mm to 30mm wide.

Select a colour of **Spectrum Futura S-25** silicone to match the grout for all movement and perimeter joints.

Follow application instructions on packaging and PDS.

WP MS-PU

Polyurethane Sealant



WP-1 PINK

Class III SBR Waterproofing Membrane



EP-2

2-Part Epoxy Primer & Moisture Barrier



ADH-33

Rubber Modified C2ETS1



ADH-44

Powder Mastic C2ETS1



ADH-55

High Polymer C2ETS2



ADH-66 Light
Lightweight C2ETS2



EZE-Clip

Tile Laying System



Spectrum Futura

Lightweight Coloured Grout



Spectrum Futura S-25

Sanitary Grade Acetoxy Silicone



SYSTEM WARRANTY

ACT Australia Pty Ltd guarantee this system for 15 years when installation is done in accordance with the standards and codes listed in this document, and full installation system has been followed.

This guarantee applies for the time of application and covers only the cost of replacement materials of the original installation only when the product is proven and acknowledged to be faulty.

